

MVBA 500™

UNLIMITED MOISTURE VAPOR BARRIER
HARD-SET RESILIENT FLOORING ADHESIVE



NOW FEATURING **NO MOISTURE TESTING**

Combatting extreme moisture, **MVBA 500™** eliminates the need for moisture testing. Its safe, 1-part chemistry makes it a faster, more install-friendly alternative to 2-part epoxy systems. Engineered for heavy rolling loads and challenging environments, MVBA 500's™ waterproof design forms a robust moisture vapor barrier and can also take the punishment introduced by topical liquids.

Shelf Life: 1 Year



AVAILABLE IN 2-GALLON PAIL

PRODUCT BENEFITS

- Simple 1-part system (modified urethane)
- Strong early grab, fast-curing formula
- High-strength, waterproof bond
- Self-leveling technology reduces telegraphing
- LEED v4 contributing
 - VOC content 0.1 g/L (meets SCAQMD Rule 1168)
 - CDPH/EHLB Standard Method v1.2
 - Does not contain methylene chloride and perchloroethylene
 - Contributes to low emitting materials

APPROVED FLOORING TYPES

- LVT/LVP
- Sheet goods (vinyl, homogeneous, heterogeneous, fiberglass, felt-backed)
- Rubber (tile and sheet)
- Linoleum
- WPC/WSC
- Cork-backed hard surface
- Cork flooring
- Cork underlayment
- VCT/VET
- Stair treads (rubber and vinyl)

APPLICATION METHODS



150-260 sf/gal

Note: Coverage range dependent upon substrate composition and porosity, application method and flooring type.

CERTIFICATIONS



RH



100%

pH



5-14

MVER



N/A

OPEN TIME



0 min

WORKING TIME



45 min

CURE TIME



6 hrs

LIGHT TRAFFIC



3 hrs

HEAVY TRAFFIC



4 hrs

HEAVY ROLLING LOADS



8 hrs

NOTE: See technical data sheet for details.